



# Vibratory Roller

When it comes to site preparation whether flatwork, paving, patching or trenching nothing matches the Thomas Vibratory Roller compacting capabilities.

The 36" (914 mm) with over 2000 vpm and a high 2488 lb (1129 kg) of dynamic force means fewer passes over the work area to obtain the required compaction.

This hard packing attachment works equally as well going forward or in reverse and with up to 15° oscillation or tilt will easily follow uneven ground and slopes.

The smooth drum features an adjustable scraper bar or as optional equipment you can choose a padded roller.



- |                                |                          |
|--------------------------------|--------------------------|
| • <b>Width (overall)</b>       | <b>42" (1067 mm)</b>     |
| • <b>Drum Width</b>            | <b>36" (914 mm)</b>      |
| • <b>Height (overall)</b>      | <b>22" (559 mm)</b>      |
| • <b>Length (overall)</b>      | <b>34" (864 mm)</b>      |
| • <b>Drum Dia.</b>             | <b>20" (508 mm)</b>      |
| • <b>Vib. Per Min.</b>         | <b>2000 vpm</b>          |
| • <b>Dynamic Force</b>         | <b>2488 lb (1129 kg)</b> |
| • <b>Drum Oscillation/Tilt</b> | <b>15°</b>               |
| • <b>Approx. Weight</b>        | <b>840 lb (381kg)</b>    |

## WWW.THOMASLOADERS.COM